



**Diemme
Filtration**



Solid-liquid separation technology for industrial processes

OVERHEAD BEAM FILTER PRESS GHT

**A brand of
Aqseptence Group**

GHT 4X4 is the pull-to-close filter press with high reliability and performance



Diemme® Filtration GHT 2500

GHT 2500 is one of the biggest filter presses currently available in the world. This machine is able to dewater huge volumes of slurry reaching very low values of residual moisture thanks to its exceptional chamber volume and filtration area. The picture on the left shows 5 GHT 2500 in operation. The dimensions of the machines can be appreciated related to the man walking near them.

Performance


The GHT 4x4 is a Diemme® Filtration filter press with high productivity. The filter plates, which are hung from the upper beam, are moved automatically by a rapid shifting device equipped with a carousel system which reduces the filter presses' opening and closing sequence to the minimum.

Reliability

Four hydraulic cylinders placed on the plate pack corners ensure perfect operation and limited structural stress, even in the most unfavorable working conditions. Effectively-guarded moving parts and the use of state-of-the-art electronic interlock systems mean that the GHT 4x4 conforms to the highest operator health and safety regulations. Routine maintenance operations are simple, thanks to easy access to the filter plates, both for inspection and for filter cloth replacement.

Membrane technology

When the application requires washing stages with solvents or drying stages with compressed air, special plates with variable-volume chambers are necessary. The plate construction material varies depending on the process temperature and of the chemical composition of the product to be filtered.




Model	Working pressure (bar)		N. of installed plates		Cake volume (l)		Filtration area (m ²)		Length (mm)		Empty weight (kg)	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
1200	15	30	38	187	1251	6500	100	400	7000	16000	15000	30700
1500	15	30	81	182	5000	11000	300	700	11500	17500	31500	46000
2000	15	30	80	246	9000	25000	600	1650	11700	24700	55000	105000
2500	15	30	85	231	10000	43000	850	2200	12000	26000	79000	200000

A filter press with world-leading technology




Automatic cloth washing system



This device ensures the perfect operation of the shifting device, thanks to two brushes that lubricate the carousel chain preventing friction and jams.

Fixed header - 4 cylinders



The fixed header is made of a high-tensile steel "cellular" structure in order to best resist stress and it supports 4 hydraulic jacks which are responsible for holding the plate pack closed.

Plc



The GHT is provided with a sophisticated automation system equipped with a human-machine interface (HMI) that simplifies the monitoring of the filter operation, enables quick diagnosis of faults and allows the continual adjustment of filtration parameters in order to optimise the process to suit variable feed conditions.

Load cells



Placed under the supporting feet, load cells constantly monitor the machine weight to ensure all cakes are discharged. The throughput of each load can also be recorded for accurate production tracking.

Automatic lifting platform



Developed for large machines, the sliding hydraulic platform allows inspection of filtering elements and routine machine maintenance in a convenient, quick and safe way.

Protection of the shifting device



The plate-shifting mechanism, located inside the upper beam, is effectively protected from sludge, dust and corrosive chemicals by a continuous belt of rubber-lined cloth.

Carousel type plate shifting



The carousel plate shifting device assures quick and sequential plate movement by means of an automatic transport system controlled by an inverter.

Carousel greasing system



Reliable cloth cleaning using a robotic device ensures that optimum filtration rates are maintained.

Laser



A laser control system ensures correct plate pack alignment and stops the filter press in case of an anomaly, so that any damage can be avoided.

A structure designed for long life






Total Traction

Different from the traditional push-type system, the "total traction" system does not transmit any stress to the upper beam, which is only subjected to the weight of plates supported from it. In fact, the forces applied by the closing device are subjecting the tie beams to tension, which avoids stress on the frame and consequently, the risk of structural deformation.

Maximum safety

The frame is conservatively designed so that the safety threshold of the material is far above the maximum stress experienced during normal operation. The upper beam is non-deformable and its maximum deflection is equal to 1/1000 of its span, even in the most severe working conditions.



Aqseptence Group srl
Filtration and Thickening Systems

Via Gessi 16
48022 Lugo
Italy
Phone +39 0545 20611
Fax +39 0545 30358
info.diemmefiltration@aqseptence.com

www.aqseptence.com